Samsung Odyssey OLED G9 S49DG934SU(LS49DG934SUXEN)

Samsung Odyssey OLED G9 S49DG934SU - G93SD Series - OLED monitor - gaming - curved - 49" - 5120 x 1440 Dual Quad HD @ 240 Hz - 250 cd/m² - 1000000:1 - HDR10+ Gaming, HDR10 -0.03 ms - DisplayPort, Micro HDMI, HDMI - silver



Experience immersive gaming and breathtaking visuals with the Samsung Odyssey OLED G9. This 49-inch OLED monitor features a native resolution of 5120 x 1440 and a V-Sync rate of 240 Hz, offering clarity and responsiveness for an engaging gaming experience. The monitor's screen curvature of 1800R enhances depth perception to fully engage the player in the gaming action, while Quantum Dot Technology delivers rich colors supported by 1 billion color hues. With features like Eye Saver Mode and Flicker-Free technology, prolonged usage becomes comfortable and strain-free.

Equipped with a USB hub and several connection options, including HDMI and DisplayPort, this monitor accommodates various devices with ease. The advanced HDR capabilities ensure bright and dynamic visuals, perfect for both gaming and multimedia consumption. Complemented by a range of customizable settings, including height and tilt adjustments, the Samsung Odyssey OLED G9 adapts to any workspace, providing a versatile solution for gamers and content creators alike.

Key Selling Points

49-inch diagonal size with a native resolution of 5120 x 1440
240 Hz V-Sync rate for high refresh rates in gaming
1800R curved screen enhances immersive visuals
Quantum Dot Technology supports 1 billion colors
Flicker-Free technology and Eye Saver Mode for comfortable viewing

Product Features

Stunning display quality

The Samsung Odyssey OLED G9 features OLED technology that offers vibrant visuals with a pixel pitch of 0.234 mm. With an impressive image contrast ratio of 1000000:1 and a brightness level of 250 cd/m2, the display excels in delivering lifelike images.

Seamless gaming experience

This monitor supports AMD FreeSync Premium Pro, providing adaptive sync technology that reduces screen tearing and stuttering for smooth gameplay. The response time of 0.03 ms ensures that gamers experience rapid action without delay, enhancing performance.

Multifunctional connectivity options

Several interface options including HDMI, DisplayPort, and USB-C make it simple to connect various devices. The built-in USB 3.2 Gen 1 hub further aids in connectivity of peripherals, streamlining the gaming and work setup.

Ergonomic adjustments

The monitor features height adjustment and tilt capabilities, allowing users to customize their setup for optimal comfort. The range of adjustments promotes ergonomic viewing, reducing fatigue during long gaming or work sessions.

Enhanced visual features

CoreSync lighting design and picture-in-picture capabilities create an engaging user experience. With features like dual-screen viewing and darkness compensation, this monitor is tailored for a captivating and immersive environment.

Main Specifications

Product Description	Samsung Odyssey OLED G9 S49DG934SU - G93SD Series - OLED monitor - curved - 49" - HDR
Device Type	OLED monitor - 49"
Energy Label QR Code URL	Https://eprel.ec.europa.eu/qr/2051150
Energy Class	Class G
Energy Consumption per Year	89 kWh
Curved Screen	Yes
Adaptive-Sync Technology	AMD FreeSync Premium Pro
Features	USB 3.2 Gen 1/USB-C hub
Aspect Ratio	32:9
Native Resolution	Dual Quad HD 5120 x 1440 at 240 Hz

Pixel Pitch	0.234 mm
Brightness	250 cd/m ²
Contrast Ratio	100000:1
HDR Capable	HDR10+ Gaming, HDR10
Response Time	0.03 ms (grey-to-grey)
Gaming	Yes
Colour Support	1 billion colours
Colour Gamut	99% DCI-P3 (CIE 1976)
Input Connectors	DisplayPort, Micro HDMI, HDMI
Display Position Adjustments	Height, tilt
Screen Coating	Anti-glare
Voltage	AC 100-240 V
Colour	Silver
Dimensions (WxDxH) - with stand	119.47 cm x 28.41 cm x 52.93 cm
Weight	12.6 kg
Compliant Standards	UL Glare Free

Extended Specification

General

Display Type	OLED monitor / OLED
Energy Label QR Code URL	Https://eprel.ec.europa.eu/qr/2051150
Energy Class	Class G
Energy Class (HDR)	Class G
Energy Consumption per Year	89 kWh
Diagonal Size	49"
Curved Screen	Yes (1800R)
Adaptive-Sync Technology	AMD FreeSync Premium Pro
Built-in Devices	USB 3.2 Gen 1/USB-C hub
Aspect Ratio	32:9
Native Resolution	Dual Quad HD 5120 x 1440 at 240 Hz
Pixel Pitch	0.234 mm
Brightness	250 cd/m ²
Contrast Ratio	1000000:1
HDR Format	HDR10+ Gaming, HDR10
Colour Support	1 billion colours
Colour Gamut	99% DCI-P3 (CIE 1976)
Response Time	0.03 ms (grey-to-grey)
Gaming	Yes
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare
Features	Eye Saver Mode, Flicker Free technology, Picture-in-Picture, Dual-screen viewing, Quantum Dot Technology, Image Size, power off timer, Darkness compensation, Virtual AIM Point, CoreSync lighting design, Super Arena gaming experience, Auto Source Switch+, Factory Tunning, Factory Calibration Report, Core lighting+ design
Colour	Silver

Dimensions (WxDxH)119.47 cm x 28.41 cm x 52.93 cm - with standWeight12.6 kgMiscellaneousCables Included1 x USB-C cable 1 x DisplayPort cableCompliant StandardsUL Glare FreePowerInput VoltageAC 100-240 VPower Consumption SDR (On mode)61 kWh/1000hPower Consumption HDR (On mode)75 kWh/1000hPower Consumption (Typica)61 WattPower Consumption (Max)220 WattPower Consumption (Max)200 WattPower Consumption (Max)0.5 WattPower Consumption (Typica)0.5 WattPower Consumption (Typica)0.5 WattPower Consumption (Typica)0.5 WattPower Consumption (Typica)0.5 WattPower Consumption (Theopen 200 Watt0.5 WattPower Consumption (Theopen 200 Watt)0.5 WattPower Consumption (Theopen 200 Watt)0.5 WattPower Consumption (Theopen 200 Watt)0.5 WattPower Consumption Start (MbCP 2.2) (HDMT (HDCP 2.2) (Mcro HDMT (HDCP 2.2) (USP-CInterfacesWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 22.6 kgPomerions & Weight Detals12.5 cmShipping Meth13.5 cm <trr>Sh</trr>		
HiscellaneousCables Included1 × USB-C cable 1 1 × DisplayPort cableCompliant StandardsUL Giare FreePowerInput VoltageAC 100-240 VPower Consumption SDR (on mode)61 kWh/1000hPower Consumption Typical61 kWh/1000hPower Consumption (Typical)61 WattPower Consumption (Typical)61 WattPower Consumption Stand by Over Consumption Stand	Dimensions (WxDxH)	119.47 cm x 28.41 cm x 52.93 cm - with stand
Cables Included 1 x USB-C cable { 1 x DisplayPort cable Compliant Standards UL Glare Free Power Input Voltage AC 100-240 V Power Consumption SDR (On mode) 61 kWh/1000h Power Consumption HDR (On mode) 75 kWh/1000h Power Consumption (Typical) 61 Watt Power Consumption (Off Mode) 0.3 Watt Power Consumption (Off Mode) 0.3 Watt Power Consumption (Mode) 0.3 Watt Environmental Parameters 10 °C Mino Operating Temperature 40 °C Humidity Range Operating 10 °C Max Operating Temperature 40 °C Interfaces DisplayPort 1.4 (HDCP 2.2) { HDMI (HDCP 2.2) { Micro HDMI (HDCP 2.2) { USB-C Dimensions & Weight Details With stand - width: 119.47 cm - depth: 28.41 cm - height: 32.93 cm - weight: 36.5 cm - weight: 36.5 cm - weight	Weight	12.6 kg
Compliant Standards UL Glare Free Power Input Voltage AC 100-240 V Power Consumption SDR (on mode) G1 kWh/1000h Power Consumption HDR (on mode) 75 kWh/1000h Power Consumption (Typical) 61 Watt Power Consumption (Mode) 20 Watt Power Consumption (Mode) 0.5 Watt Power Consumption (Off Mode) 0.3 Watt Power Consumption (Off Mode) 0.3 Watt Power Consumption Temperature 10 °C Min Operating Temperature 40 °C Humidity Range Operating 10 -80% (non-condensing) Consectivity DisplayPort 1.4 (HDCP 2.2) HDMI (HDCP 2.2) MICro HDMI (HDCP 2.2) USB-C Interfaces DisplayPort 1.4 (HDCP 2.2) HDMI (HDCP 2.2) MICro HDMI (HDCP 2.2) USB-C Dimensions & Weight Details With stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details With stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Shipping Width 135.2 cm Shipping Width 135.2 cm Shipping Weight 24 cm Shipping Weight 18.1 kg Mechanical With stand - Width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg	Miscellaneous	
Compliant Standards UL Glare Free Power Input Voltage AC 100-240 V Power Consumption SDR (on mode) G1 kWh/1000h Power Consumption HDR (on mode) 75 kWh/1000h Power Consumption (Typical) 61 Watt Power Consumption (Mode) 20 Watt Power Consumption (Mode) 0.5 Watt Power Consumption (Off Mode) 0.3 Watt Power Consumption (Off Mode) 0.3 Watt Power Consumption Temperature 10 °C Min Operating Temperature 40 °C Humidity Range Operating 10 -80% (non-condensing) Consectivity DisplayPort 1.4 (HDCP 2.2) HDMI (HDCP 2.2) MICro HDMI (HDCP 2.2) USB-C Interfaces DisplayPort 1.4 (HDCP 2.2) HDMI (HDCP 2.2) MICro HDMI (HDCP 2.2) USB-C Dimensions & Weight Details With stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details With stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Shipping Width 135.2 cm Shipping Width 135.2 cm Shipping Weight 24 cm Shipping Weight 18.1 kg Mechanical With stand - Width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg		
Power Input Voltage AC 100-240 V Power Consumption SDR (on mode) 61 kWh/1000h Power Consumption TDR (on mode) 51 kWh/1000h Power Consumption TDR (on mode) 51 kWh/1000h Power Consumption TOPice) 61 Watt Power Consumption SDR (on mode) 50 kWh/1000h Power Consumption TOPice) 61 Watt Power Consumption SDR (on mode) 50 Watt Power Consumption SDR (on tower Consumption SDR (on Power SDR (SDR) Interfaces DisplayPort 1.4 (HDCP 2.2) { HDMI (HDCP 2.2) { Micro HDMI (HDCP 2.2) { USP-C		
Input VoltageAC 100-240 VPower Consumption SDR (On mode)61 kWh/1000hPower Consumption SDR (On mode)75 kWh/1000hPower Consumption (Typical)61 WattPower Consumption (Max)220 WattPower Consumption (Max)220 WattPower Consumption (Max)0.5 WattPower Consumption (Off Mode)0.3 WattEnvironmental Parameters10 °CMin Operating Temperature40 °CHumidity Range Operating10 - 80% (non-condensing)ConnectivityJisplayPort 1.4 (HDCP 2.2) ! HDMI (HDCP 2.2) ! Micro HDMI (HDCP 2.2) ! USB-C upstream ! 2 x USB-C 3.2 Gen 1 downstream ! Headphone jack (mini-jack)Dimensions & Weight DetailsWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight DetailsLife kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight DetailsLife kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight DetailsLife kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight DetailsLife kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDisplay Position AdjustmentHeight, tiltShipping Weight135.2 cmShipping Weight135.2 cmShipping Weight14.1 cmShipping Weight18.1 kgDisplay Position AdjustmentHeight,	Compliant Standards	UL Glare Free
Power Consumption SDR (On mode)61 kWh/1000hPower Consumption HDR (On mode)75 kWh/1000hPower Consumption (Typical)61 WattPower Consumption (Max)220 WattPower Consumption Max)200 WattPower Consumption (Max)0.5 WattPower Consumption (Off Mode)0.3 WattEnvironmental Parameters0 °CMin Operating Temperature40 °CHumidity Range Operating10 - 80% (non-condensing)EnterfacesDisplayPort 1.4 (HDCP 2.2) { HDMI (HDCP 2.2) { Micro HDMI (HDCP 2.2) { USB-C upstream { 2 x USB-C 3.2 Gen 1 downstream { Headphone jack (mini-jack)Dimensions & Weight DetailsWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg { Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight Details135.2 cmShipping Width135.2 cmShipping Width14.4 (aShipping Weight14.1 kgDisplay Position AdjustmentHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Power	
mode)6.1 kWin/1000inPower Consumption HDR (On mode)75 kWh/1000inPower Consumption (Typical)61 WattPower Consumption (Max)220 WattPower Consumption Stand by0.5 WattPower Consumption Stand by0.3 WattPower Consumption (Off Mode)0.3 WattPower Consumption Stand by0.5 WattPower Consumption Stand by0.5 WattPower Consumption Stand by0.3 WattPower Consumption Stand by0.5 WattMin Operating Temperature10 °CMax Operating Temperature40 °CHumidity Range Operating10 - 80% (non-condensing)DisplayPort 1.4 (HDCP 2.2) ; HDMI (HDCP 2.2) ; Micro HDMI (HDCP 2.2) ; USB-CDisplayPort 1.4 (HDCP 2.2) ; More HDMI (HDCP 2.2) ; USB-CDisplay Both12.6 kg ; Without stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ; Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight Details135.2 cmShipping Weight135.2 cmShipping Height24 cmShipping Weight18.1 kgDisplay Position AdjustmentsHeight, tiltDisplay Position AdjustmentsHeight, tilt	Input Voltage	AC 100-240 V
mode)75 kmin 10001Power Consumption (Typical)61 WattPower Consumption (Max)220 WattPower Consumption (Max)0.5 WattPower Consumption (Off Mode)0.3 WattEnvironmental Parameters10 °CMin Operating Temperature40 °CHumidity Range Operating10 °CMax Operating Temperature40 °CHumidity Range Operating10 °CInterfacesDisplayPort 1.4 (HDCP 2.2) ; HDMI (HDCP 2.2) ; Micro HDMI (HDCP 2.2) ; USB-C upstream ; 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack)Dimensions & WeightWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: weight: 8.8 kgDimensions & Weight DetailsVith stand - width: 119.47 cm - depth: 28.41 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight (Shipping)135.2 cmShipping Width135.2 cmShipping Weight47.4 cmShipping Weight18.1 kgMechanical19.1 kgDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm		61 kWh/1000h
Power Consumption (Max) 220 Watt Power Consumption Stand by 0.5 Watt Power Consumption (Off Mode) 0.3 Watt Environmental Parameters Image: Consumption (Off Mode) Min Operating Temperature 10 °C Max Operating Temperature 40 °C Humidity Range Operating 10 - 80% (non-condensing) Connectivity Interfaces DisplayPort 1.4 (HDCP 2.2) ; HDMI (HDCP 2.2) ; Micro HDMI (HDCP 2.2) ; USB-C upstream ; 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack) Dimensions & Weight Uith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ; Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details Vith stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details 135.2 cm Shipping Width 135.2 cm Shipping Weight 24 cm Shipping Weight 18.1 kg Mechanical Display Position Adjustments Pisplay Position Adjustments Height, tilt Tilt Angle -2/+15 Height Adjustment 120 mm		75 kWh/1000h
Power Consumption Stand by 0.5 Watt Power Consumption (Off Mode) 0.3 Watt Environmental Parameters In o °C Min Operating Temperature 40 °C Humidity Range Operating 10 - 80% (non-condensing) Connectivity Interfaces Interfaces DisplayPort 1.4 (HDCP 2.2) HDMI (HDCP 2.2) Micro HDMI (HDCP 2.2) USB-C upstream 2 x USB-C 3.2 Gen 1 downstream Headphone jack (mini-jack) Dimensions & Weight Uith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details With stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details 135.2 cm Shipping Width 135.2 cm Shipping Depth 47.4 cm Shipping Weight 24 cm Shipping Weight 24 cm Shipping Weight 18.1 kg Mechanical Pisplay Position Adjustments Pisplay Position Adjustments Height, tilt Tilt Angle -2/+15 Height Adjustment 120 mm	Power Consumption (Typical)	61 Watt
Power Consumption (Off Mode) 0.3 Watt Environmental Parameters Image: Consumption (Off Mode) Min Operating Temperature 10 °C Max Operating Temperature 40 °C Humidity Range Operating 10 - 80% (non-condensing) Connectivity Interfaces Interfaces DisplayPort 1.4 (HDCP 2.2) ¦ HDMI (HDCP 2.2) ¦ Micro HDMI (HDCP 2.2) ¦ USB-C upstream ¦ 2 x USB-C 3.2 Gen 1 downstream ¦ Headphone jack (mini-jack) Dimensions & Weight DisplayPort 1.4 (HDCP 2.2) ¦ HDMI (HDCP 2.2) ! Micro HDMI (HDCP 2.2) ¦ USB-C upstream ¦ 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack) Dimensions & Weight DisplayPort 1.4 (HDCP 2.2) ¦ HDMI (HDCP 2.2) ! Micro HDMI (HDCP 2.2) ! USB-C upstream ¦ 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack) Dimensions & Weight Display Port 1.4 (HDCP 2.2) ! Micro HDMI (HDCP 2.2) ! USB-C upstream ' 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack) Dimensions & Weight Details With stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ! Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details 135.2 cm Shipping Depth 47.4 cm Shipping Weight 24 cm Shipping Weight 18.1 kg Mechanical Height, tilt Display Position Adjus	Power Consumption (Max)	220 Watt
Environmental Parameters Min Operating Temperature 10 °C Max Operating Temperature 40 °C Humidity Range Operating 10 - 80% (non-condensing) Connectivity interfaces Interfaces DisplayPort 1.4 (HDCP 2.2) HDMI (HDCP 2.2) Micro HDMI (HDCP 2.2) USB-C upstream 2 x USB-C 3.2 Gen 1 downstream Headphone jack (mini-jack) Dimensions & Weight Uist stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details Vith stand - width: 119.47 cm - depth: 28.41 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Obtails 135.2 cm Shipping Width 135.2 cm Shipping Depth 47.4 cm Shipping Width 135.1 kg Shipping Weight 18.1 kg Dimensional Meight 24 cm Shipping Weight 18.1 kg Display Position Adjustments Height, tilt Tilt Angle -2/+15 Height Adjustment 120 mm	Power Consumption Stand by	0.5 Watt
Min Operating Temperature10 °CMax Operating Temperature40 °CHumidity Range Operating10 - 80% (non-condensing)ConnectivityInterfacesDisplayPort 1.4 (HDCP 2.2) ; HDMI (HDCP 2.2) ; Micro HDMI (HDCP 2.2) ; USB-C upstream ; 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack)Dimensions & WeightWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ; Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight DetailsXith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ; Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight ObtailsXith stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - shipping WidthShipping Width135.2 cmShipping Width135.2 cmShipping Weight24 cmShipping Weight18.1 kgMechanicalDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Power Consumption (Off Mode)	0.3 Watt
Max Operating Temperature40 °CHumidity Range Operating10 - 80% (non-condensing)ConnectivityInterfacesDisplayPort 1.4 (HDCP 2.2) ; HDMI (HDCP 2.2) ; Micro HDMI (HDCP 2.2) ; USB-C upstream ; 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack)Dimensions & WeightWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ; Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight ObtailsWith stand - width: 119.47 cm - depth: 28.41 cm - height: 36.5 cm - 	Environmental Parameters	
Humidity Range Operating10 - 80% (non-condensing)ConnectivityInterfacesDisplayPort 1.4 (HDCP 2.2) ; HDMI (HDCP 2.2) ; Micro HDMI (HDCP 2.2) ; USB-C upstream ; 2 x USB-C 3.2 Gen 1 downstream ; Headphone jack (mini-jack)Dimensions & WeightWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ; Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight DetailsWith stand - width: 119.47 cm - depth: 28.41 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight ObtailsWith stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight Obtails135.2 cmShipping Depth47.4 cmShipping Height24 cmShipping Weight18.1 kgMechanicalDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Min Operating Temperature	10 °C
Connectivity Interfaces DisplayPort 1.4 (HDCP 2.2) ! HDMI (HDCP 2.2) ! Micro HDMI (HDCP 2.2) ! USB-C upstream ! 2 x USB-C 3.2 Gen 1 downstream ! Headphone jack (mini-jack) Dimensions & Weight With stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ! Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details With stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ! Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Details 135.2 cm Shipping Depth 135.2 cm Shipping Depth 47.4 cm Shipping Weight 24 cm Shipping Weight 18.1 kg Mechanical 19.1 kg Display Position Adjustments Height, tilt Tilt Angle -2/+15 Height Adjustment 120 mm	Max Operating Temperature	40 °C
Interfaces DisplayPort 1.4 (HDCP 2.2) ¦ HDMI (HDCP 2.2) ¦ Micro HDMI (HDCP 2.2) ¦ USB-C upstream ¦ 2 x USB-C 3.2 Gen 1 downstream ¦ Headphone jack (mini-jack) Dimensions & Weight With stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ¦ Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight Chipping With stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ¦ Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kg Dimensions & Weight (Shipping) Jisplay Bopth Shipping Depth 47.4 cm Shipping Height 24 cm Shipping Weight 18.1 kg Mechanical Height, tilt Display Position Adjustments Height, tilt Tilt Angle -2/+15 Height Adjustment 120 mm	Humidity Range Operating	10 - 80% (non-condensing)
Interfacesupstream ¦ 2 x USB-C 3.2 Gen 1 downstream ¦ Headphone jack (mini-jack)Dimensions & WeightWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg ¦ Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight (Shipping)Jis.2 cmShipping Depth47.4 cmShipping Weight24 cmShipping Weight18.1 kgMechanicalJis.1 kgDisplay Position AdjustmentsHeight, tilt 120 mmDisplay Adjustment120 mm	Connectivity	
Dimensions & Weight DetailsWith stand - width: 119.47 cm - depth: 28.41 cm - height: 52.93 cm - weight: 12.6 kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight (Shipping)Image: Shipping Weight (Shipping)Shipping Width135.2 cmShipping Depth47.4 cmShipping Height24 cmShipping Weight18.1 kgMechanicalImage: Shipping WeightDisplay Position AdjustmentsHeight, tiltHeight Adjustment120 mm	Interfaces	
Dimensions & Weight Details12.6 kg Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm - weight: 8.8 kgDimensions & Weight (Shipping)IShipping Width135.2 cmShipping Depth47.4 cmShipping Height24 cmShipping Weight18.1 kgMechanicalIDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Dimensions & Weight	
Shipping Width135.2 cmShipping Depth47.4 cmShipping Height24 cmShipping Weight18.1 kgMechanicalEmpiricalDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Dimensions & Weight Details	12.6 kg ¦ Without stand - width: 119.47 cm - depth: 18.08 cm - height: 36.5 cm -
Shipping Depth47.4 cmShipping Height24 cmShipping Weight18.1 kgMechanicalHeight, tiltDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Dimensions & Weight (Shipping)	
Shipping Height24 cmShipping Weight18.1 kgMechanicalImage: Shipping Yosition AdjustmentsHeight, tiltDisplay Position Adjustments4 -2/+15Height Adjustment120 mm	Shipping Width	135.2 cm
Shipping Weight18.1 kgMechanicalHeight, tiltDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Shipping Depth	47.4 cm
MechanicalDisplay Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Shipping Height	24 cm
Display Position AdjustmentsHeight, tiltTilt Angle-2/+15Height Adjustment120 mm	Shipping Weight	18.1 kg
Tilt Angle-2/+15Height Adjustment120 mm	Mechanical	
Tilt Angle-2/+15Height Adjustment120 mm	Display Position Adjustments	Height, tilt
Height Adjustment 120 mm		
	Height Adjustment	120 mm
	VESA Mounting Interface	100 x 100 mm

 $\ast {\rm TD}$ SYNNEX is not responsible for errors in the documentation of products.