

Dell Pro P P2426HE (DELL-P2426HE)

Dell Pro P P2426HE - LED monitor - 24" (23.8" viewable) - 1920 x 1080 Full HD (1080p) @ 120 Hz - IPS - 300 cd/m² - 1500:1 - 5 ms - HDMI, DisplayPort, USB-C - with 3 years Advanced Exchange Service



Main Specifications

Product Description	Dell Pro P P2426HE - LED monitor - Full HD (1080p) - 24"
Device Type	LED-backlit LCD monitor - 24"
Energy Label QR Code URL	https://eprel.ec.europa.eu/qr/2499643
Energy Class	Class D
Features	USB-C hub, USB PD 100 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 120 Hz
Pixel Pitch	0.2745 mm
Brightness	300 cd/m ²
Contrast Ratio	1500:1
Response Time	5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal)
Colour Support	16.7 million colours
Colour Gamut	99% sRGB (CIE 1931), 99% BT.709 (CIE 1931)
Input Connectors	HDMI, DisplayPort, USB-C
Built-in Ethernet	Yes
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - with stand (highest position)	53.864 cm x 18.175 cm x 49.653 cm
Weight	4.95 kg
Environmental Standards	ENERGY STAR Qualified
Compliant Standards	Plug and Play, RoHS, BFR-free, PVC-free
Bundled Services	3 years Advanced Exchange Service

Extended Specification

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Label QR Code URL	https://eprel.ec.europa.eu/qr/2499643
Energy Class	Class D
Diagonal Size	24"
Viewable Size	23.8"
Built-in Devices	USB-C hub
USB Power Delivery	100 Watt

Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 120 Hz
Pixel Pitch	0.2745 mm
Pixel Per Inch	93
Brightness	300 cd/m²
Contrast Ratio	1500:1
Colour Support	16.7 million colours
Colour Gamut	99% sRGB (CIE 1931), 99% BT.709 (CIE 1931)
Response Time	5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal)
Vertical Refresh Rate	48 - 120 Hz
Horizontal Refresh Rate	30 - 135 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	Wide Viewing Angle, Dell ComfortView Plus, Low Blue Light technology, LED edgelight system, Dell Easy Arrange, Mercury free, arsenic-free glass
Dimensions (WxDxH)	53.864 cm x 18.175 cm x 49.653 cm - with stand (highest position)
Weight	4.95 kg

Manufacturer Warranty

Bundled Services	3 years Advanced Exchange Service
------------------	-----------------------------------

Miscellaneous

Features	VESA interface support, security lock slot (cable lock sold separately), integrated cable management
Cables Included	1 x USB-C cable - 1.8 m
Compliant Standards	Plug and Play, RoHS, BFR-free, PVC-free
Security Slot Type	Kensington security slot

Power

Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	13.8 kWh/1000h
Power Consumption (Typical)	13.2 Watt
Power Consumption (Max)	215 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.3 Watt

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

Connectivity

Interfaces	HDMI (HDCP 1.4) ¦ DisplayPort (HDCP 1.4) ¦ DisplayPort output (HDCP 1.4) ¦ USB-C upstream/DisplayPort 1.4 Alt Mode with Power Delivery (power up to 100W) ¦ 2 x USB downstream (Type A) ¦ LAN (RJ-45) ¦ USB-C downstream (data only)
------------	--

Dimensions & Weight

Dimensions & Weight Details	With stand (highest position) - width: 53.864 cm - depth: 18.175 cm - height: 49.653 cm - weight: 4.95 kg ¦ With stand (lowest position) - width: 53.864 cm - depth: 18.175 cm - height: 36.4 cm - weight: 4.95 kg ¦ Without stand - width: 53.864 cm - depth: 5.003 cm - height: 31.423 cm - weight: 3.45 kg
-----------------------------	---

Dimensions & Weight (Shipping)

Shipping Weight	6.96 kg
-----------------	---------

Mechanical

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	90
Rotation Angle	180
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm

Sustainability Information

ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0

*TD SYNnex is not responsible for errors in the documentation of products.